

Codice articolo Product code:	2002028
Descrizione Description:	PATCH PANEL TELEFONICO 25 PRESE RJ45 CATEGORIA 3 VOICE PATCH PANEL 25 CATEGORY 3 RJ45 PORTS



Descrizione

Pannello telefonico CCS di Categoria 3 a 25 posizioni precablato con 25 prese RJ45 non schermate a 6 conduttori con sistema di terminazione IDC 110.

Prestazioni

Standards ISO/IEC 11801-1/2:2017 (Ed. 1.0)
EN 50173-1:2011
ANSI/TIA-568-C.2

Caratteristiche costruttive

Struttura	- Telaio in acciaio - Modularità 25 posizioni - 5 moduli a 5 posizioni - Supporto posteriore per la gestione del cablaggio
Prese	25 prese preinstallate CAT. 3 RJ45 non schermate a 4 conduttori con sistema di terminazione IDC 110
Installazione	Su rack 19"
Ingombro	1 unità rack
Colore	Nero
Messa a terra	Tramite un cavo rivettato ai lati del pannello
Identificazioni e loghi	Logo CCS

Condizioni di utilizzo e stoccaggio

Temperatura di stoccaggio	Da -40°C a +80°C
Temperatura di lavoro	Da -10°C a +60°C
Umidità relativa	Max. 93% senza condensazione

Confezionamento

Dimensioni scatola	560x140x700 mm
Peso	Approx. 1 kg
Ogni confezione include	- 1 pannello CCS a 25 posizioni precablato con 25 prese Cat 3 RJ45 non schermate a 4 conduttori - Fascette di fissaggio cavi

Description

CAT 3 CCS 25-port voice patch panel, preloaded with 25 unshielded 6-pin RJ45 jacks with IDC 110 termination system.

Performance

Approvals ISO/IEC 11801-1/2:2017 (Ed. 1.0)
EN 50173-1:2011
ANSI/TIA-568-C.2

Construction characteristics

Structure	- Steel frame - 25ports modularity - 5 modules with 5 ports each - Rear cable management
Jacks	25 pre-installed CAT 3 4-pin RJ45 unshielded jacks with IDC 110 termination system
Mounting	19" rack
Size	1 rack unit
Colour	Black
Earthing	Via a riveted cable on the sides of the drawer
Printing	CCS Logo

Environmental conditions

Storage temperature	From -40°C to +80°C
Operating temperature	From -10°C to +60°C
Relative humidity	Maximum non-condensing 93%

Packaging

Box dimension	560x140x700 mm
Weight	Approx. 1 kg
Each package includes	- 1 CCS 25-port patch panel, preloaded with 25 Cat. 3 4-pin unshielded RJ45 jacks - Cable ties

Codice articolo Product code:	2002028
Descrizione Description:	PATCH PANEL TELEFONICO 25 PRESE RJ45 CATEGORIA 3 VOICE PATCH PANEL 25 CATEGORY 3 RJ45 PORTS

DISEGNO TECNICO/TECHNICAL DRAWINGS

