

OneView KVM switch with Monitor 17"

OneView
KVM SWITCH



Benefits:

★★★★★

★★★★★

★★★★★

★★★★★

★★★★★

★★★★★

All in one with additional switch

Combo USB/PS2 cable included

Quick mounting

1U

Metal case

International qwerty keyboard



KVM OneView

Strong, safe and scalable



The TecnoSteel KVM is a simple and cheap solution for server and computers management and control in small and medium server room.

KVM can be mounted in most of the standard 19" racks thanks to the bays supplied with the instrument and fill 1U.

The KVM switch (optional), thanks to the Combi cable USB/PS2 provided in the package, allows the easy connection to 8 or 16 servers both with USB and PS2 for keyboard and mouse. Each switch can be linked to 32 additional switches. This means that it will be possible monitoring up to 512 servers.

The physical safe is granted by a lock with key lock and by a safety mechanical system which avoid the accidental closing of the console. In addition, the logical access is protected by passwords: one primary and 7 secondary.

The integrated 17" LCD monitor is at active matrix high resolution. The robust Italian keyboard with 105 thin keys with soft-touch membrane and the integrated touch-pad mouse complete the instrument.



SPACE

OneView fill one unit.



INSTALLATION

KVM can be mounted in most of the standard 19". Thanks to the supplied guides it adapts to any depth.

**SAFETY****Mechanical safety**

The physical safe is granted by a lock with key lock and by a safety mechanical system which avoid the accidental closing of the console.

The logical access is protected by passwords: one primary and 7 secondary.

Main characteristics

- DB-15 KVM with Italian keyboard, VGA cable and mouse
- 1U mounting in 19" rack
- Quick and easy installation
- No SW or driver required
- Supports all computers both at the start up and in operating commutation
- A beep indicates the connection keyboard-PC or the refresh to the initial conditions
- Simple and user-friendly through the OID keys
- The logical access is protected by passwords: one primary and 7 secondary
- Use of insulation technology and name simulation, to avoid diaphony between keyboard and mouse.
- Auto Scan Mode
- The ports integrated in the switch allows the use of a single port of the PC
- Auto scan of the linked units
- Possible customization of the shortcut keys (Scroll/lock, Cap Lock.....)
- Other keyboards not necessary
- Support the safe protection with 2 password and the name of the computer search

Electrical Safety:
FCC, CE, CCC



Interchangeable Switch



Interchangeable Switches

Direct connection to PC	8 for 8 ports model	16 for 16 ports model
Maximum connection to PC	256 for 8 ports model	512 for 16 ports model
Management ports	display, keyboard and mouse	
OSD Switch	supported	
Switch mode	Hotkey - OSD menu	
Scan time switch	1-255 sec (editable through OSD)	
Pre-electronic key	server selection through function keys use	
Power pack	AC 100V-240V 47-63Hz Power 1W	
Case material	Anticorrosion steel	
Color	Black	
Size	180mm x 438mm x 44mm	
Weight	8 porte 6,55KG - 16 porte 8,45KG	
Environment conditions	Stocking temperature -30°C~65°C Operating temperature -10°C~60°C Humidity 0%~80% RH	
Safe certifications	CCC /FCC/ CE	
Ports	1*VGA monitor; 1*PS/2 keyboard; 1* PS/2 mouse.	
Supported connection to PC	15 Pin VGA Port (female) 6 Pin PS/2 Keyboard (female) 6 Pin PS/2 Mouse (female)	
Other characteristics	<ul style="list-style-type: none"> • Cascade switches up to 8/16 levels and switch mix DB-15 KVM • Multi plat-form Switch Mix PS/2, USB, SUN & MAC • Auto scan for PC monitoring. Flexible scan time 1.255 sec • Plug and play support, allows to add PC or moving the links for maintenance without switching off of the connected units 	

CABLES

Each switch includes
combo PS2/USB cables



INTERCHANGEABLE SWITCH

1, 8, 16 ports

Console Technical Characteristics

Case material	high resistance anticorrosion steel and aluminum
LCD display	Active matrix TFT 17" LCD
Resolution	1280x1024 @ 75 Hz
Size	480 (L) x 580 (P) x 44 (H) mm
Ratio control	700:1
Answering time	15 ms
Autoscan time	1 to 255 sec (editable through OSD)
Display colors	16 M of colors
PC interface	analogic video Sinc RGB 0.7 Vpp TTL positive or negative
Video compatibility	VGA - SVGA - XGA - SXGA
PC connection	Direct 1, max:1
Connecting cables	D-sub 15 (LCD etc. keyboards, mouse), supports ODS
Power transformer	AC 100 - 240V, 47~63 Hz, 35W
Transformer output	12V DC
Operating temperature	0°C ÷ 50°C
Operating humidity	0% ÷ 95%
Stocking temperature	-20°C ÷ 60°C
Stocking humidity	0% ÷ 95%
Net weight	21,7 Kg
Gross weight	±26,5 Kg
Certifications	CE, FCC, CCC
MTBF	60,000h



OTHER CHARACTERISTICS
External power supplied

Code	Characteristics
F9857N	KVM with 1 port switch module
F9808N	8 ports switch module
F9816N	16 ports switch module

The information herein contained are correct at the time of issue and are subjected to changes without any notice. The images are only intended to illustrate the product and can change at the manufacturer's discretion.

tecnosteel
IT endless solutions

Head quarter | Tecnosteel s.r.l.

Via Pret 12
21020 Brunello (Va)
Italy
tel. +39 0332 46 26 04
fax: +39 0332 46 26 09
info@tecnosteel.it
www.tecnosteel.it



France | Tecnosteel France

ZI Vigne aux Loups
4, rue De Bossuet
91160 Longjumeau - France
ph. +33 (0)1 69 74 17 35
fax +33 (0)1 64 48 31 85
info@tecnosteel.fr
www.tecnosteel.fr

Polska | Tecnosteel Sp. z.o.o

ul. Kosciuszki 6,
PL - 97500 Radomsko
ph. +48 (0)44 682 33 00
fax: +48 (0)44 682 33 00
info@tecnosteel.pl
www.tecnosteel.pl